Designed For Reliability...

WATER FLOW/SURFACE WATER

General

The Cable Fox Model (CFX) is HyQuest Solutions latest technology for towing an ADCP or setting up a radar system temporarily for measuring water flow. What distinguishes the CFX from other cableway systems, is its ability to operate on any existing cableway, with a main cable installed, without the need for any additional accessories.

The CFX is easily carried and can operate wirelessly up to 400 meters (1312 feet), thereby keeping the operator in a safe position, away from any hazards presented by flood waters.

In addition, the CFX is a portable unit with low power consumption allowing the user to gauge several sites in the same day without the need for any maintenance or the need to recharge the battery.

Features

- Variable traversing speed up to 0.6m/ sec (2ft/sec)
- Hoist attachment available (to adjust tether line to ADCP trimaran/board)
- In built encoder for distance measurement across stream
- Low power consumption
- Auto retrieval Feature

Specifications

Cable Fox Motor Body

- Geared Motor 320W
- Speed Drives carriage up to 0.6 m/s (2.00 ft/s)
- Distance Measurement 0.01m (0.01 ft) resolution
- Power Requirement 12V DC 18Ah battery Internal 30A auto reset fuse

Hoist (Optional)

- Lifting Capacity 100 Kg (220 lbs)
- Power Requirements Uses the above Cable Fox power (12V 18Ah) Separate internal 30A auto reset fuse
- Cable Synthetic Rope 12.2m (40ft)

Wireless Remote Control

- Controls
 - Raise / Lower Control + Battery Voltage monitoring
 - Forward / Reverse + Speed control
- **I** 1 ([
 - 16 char x 2 line with backlighting
 - Calculates horizontal distance
- Radio Frequency
 - USA 902.5 to 914.5 MHz
 - AUS 915.5 to 927.5 MHz
 - (26 channels @ 1MHz spacing)
- Operating Range 400m (1300 ft) line of sight
- Indicators
 - LEDs for comms and fault indication

- Sounder for low battery
- Power Source
 - 3 x NiMh 2.5Ah AA batteries with built-in charger (3 x AA Alkaline batteries in an emergency)
- Dimensions
 - Cable Fox: 650mm (W) x 510mm (H) x 240mm (D) [(26"(W)x 20"(H)x10"(D)
 - Mass: 35Kg (77lb)
 - Hoist: 510mm (W) x 440mm (H) x 230mm (D) [(21"(W)x 18"(H)x9"(D)
 - Mass: 23Kg (51lb)







Contact Us

General Enquiries (Australia)

Phone: +61 2 9601 2022

Email: sales@hyquestsolutions.com.au Web: www.hyquestsolutions.com.au

General Enquiries (New Zealand)

Phone: +64 (0) 7 857 0810

Email: sales@hyquestsolutions.co.nz Web: www.hyquestsolutions.co.nz